

# Large Square Rotary Stripping and Cutting Machine

WG-9850

## Features

- Mainly used for cutting and stripping EV cables and multi-layer cables;
- Servo-driven feeding mechanism with automatic centering for precise feeding;
- Unique rotary cutting unit with automatic centering correction to ensure precise cutting.
- Equipped with encoder for length and stripping length correction.
- Independent and shiftable double-head frame design enables this machine applicable to various specifications of wires;
- Function of wire saving
- Customizable as right-in, left-out configuration.
- Optional meter counter.
- Reserved MES hardware interface.

## Product Parameters

| Model                    | WG-9850L  |
|--------------------------|---|
| Stripping Range          | 6 - 120mm <sup>2</sup>                              |
| Wire OD                  | 6 - 25mm  |
| Maximum Stripping Length | Front: 400mm / Rear: 250mm                          |
| Cutting Accuracy         | 0.1%L+1   |
| Unit of Cutting Depth    | 0.01mm  |
| Max Stripping Layers     | 6 Layer   |
| Stripping Method         | Cutting Blades / Stripping Blades / Piercing Blades |
| Power Supply             | AC220V 50/60Hz                                      |
| Productivity             | 200-450pcs/h  |
| Weight                   | 400kg   |
| Dimensions               | 1500*700*1450mm                                     |



# Large Square Rotary Stripping and Cutting Machine

WG-9850L

## Features

- Mainly used for cutting and stripping EV cables and multi-layer cables;
- Servo-driven feeding mechanism with automatic centering for precise feeding;
- Unique rotary cutting unit with automatic centering correction to ensure precise cutting.
- Equipped with encoder for length and stripping length correction.
- Independent and shiftable double-head frame design enables this machine applicable to various specifications of wires;
- Function of wire saving
- Customizable as right-in, left-out configuration.
- Optional meter counter.
- Reserved MES hardware interface.

## Product Parameters

| Model                    | WG-9850L  |
|--------------------------|---|
| Stripping Range          | 6 - 200mm <sup>2</sup>                              |
| Wire OD                  | 6 - 35mm  |
| Maximum Stripping Length | Front: 400mm / Rear: 250mm                          |
| Cutting Accuracy         | 0.1%L+1   |
| Unit of Cutting Depth    | 0.01mm  |
| Max Stripping Layers     | 6 Layer   |
| Stripping Method         | Cutting Blades / Stripping Blades / Piercing Blades |
| Power Supply             | AC220V 50/60Hz                                      |
| Productivity             | 200-450pcs/h  |
| Weight                   | 450kg   |
| Dimensions               | 1500*700*1450mm                                     |

